


Guide to **Smart TRV** head compatibility with hot-water radiators







The Smart TRV* is compatible with valve bodies with dimensions of M30x1.5.



ADAPTERS SUPPLIED in:

Smart TRV con adapt – Ref. 6050686 and **Smart TRV Starter Pack** – Ref. 6053090

Adapters are available to purchase separately: **Set of 6 Smart TRV adapters** - Ref. 6200282

	Valve body		Matching adapter
Danfoss RA	Ø 19 mm		
Danfoss RAV	Ø 34 mm		
Danfoss RAVL	Ø 26 mm		
Format M28x1.5 : Comap / Herz / MMA Markaryds / TA	Ø 28 mm		
Caleffi	Ø 23 mm		
Giacomini	Ø 19,5 mm		

* To ensure that the Smart TRV head is compatible with the existing radiator, the radiator must be fitted with a thermostatic radiator valve body.

ADAPTORS NOT SUPPLIED with Delta Dore solutions

Items available on the market

	Valve body	Matching adapter
Vaillant Ref. Vaillant 700097	Ø 30,5 mm	
Oventrop Ref. Oventrop 1011445	Before 1997 : M30x1.0	
Ista Ref. Ista 9700-36.700	Ø 32 mm Thread size 1.0	
Orkli Ref. Eurotronic 700100020	Ø 28 mm Thread size 1.0	
Pettinaroli Ref. Pettinaroli EER53260	Ø 28 mm Thread size 1.5	
SAM – Slovarm 76030 adapter with a 24 mm shank	Ø 28 mm Thread size 1.5	
Ondal Ref. Ondal 700100011	Ø 38 mm Thread size 1.5	



COM3701915 - 09/2024 | Images for illustrative purposes only
Delta Dore reserves the right to modify these specifications without prior notification.

**DELTA
DORE**